



## Spiral clamp for attaching externally corrugated spiral hoses

### Properties

- practically leak-proof and firmly clamping with special bridge geometry
- easily and quickly fitted
- re-usable (threaded)
- rust-proof
- very robust
- conform to RoHS guideline

### Design, material

1. clamp band: W2 stainless steel 1.4016 = AISI 430
2. screw: W2 galvanised steel  
housing: W2 stainless steel 1.4016
3. bridge: stainless steel 1.4301/ AISI 304/ W2 (INOX)

### Suitable for Hose

AIRDUC®: 341+345, 350+351+355 MHF, HT-PUR 351+355, INOX 351+355 MHF-AS, 351+355+362 EC, 353, 355, 362 F, 363  
 PROTAPE®: 301, 310, 320, 322 EC, 326 MEMORY, 327 MEMORY, 330 MHF, 330 MHF-AS, INOX 330 MHF  
 TIMBERDUC®: 531+533+534 SE  
 CP: 450+461 PROTECT, 450, 455, 457, 459 EC, 460 461, 471 EC, 471 INOX, 472 EC, 472 INOX, 475 EC, 475 F, 480, 481, 483, 485, 486, 487


Suitable for Hose	Clamping	Band	AIRDUC®, PROTAPE®, CP ≥ 70 mm	CP
I.D.	Range	Width	Order No.	Order No.
mm	mm	mm		
13-16	9-19	5	212-0009-0000	-
15-20	13-24	5	212-0013-0000	-
18-26	17-29	5	212-0017-0000	-
20-32	20-32	5	212-0020-0000	-
30-35	27-47	9	212-0027-0000	-
38-45	35-55	9	212-0035-0000	212-0035-2002
50-55	45-65	9	212-0045-0000	-
60-65	55-75	9	212-0055-0000	-
70-75	65-85	9	212-0065-0000	-
80	75-95	9	212-0075-0000	-
90	85-105	9	212-0085-0000	-
100-102	95-115	9	212-0095-0000	-
110-115	105-125	9	212-0105-0000	-
120-127	115-135	9	212-0115-0000	-
130	125-145	9	212-0125-0000	-
140	135-155	9	212-0135-0000	-
150-152	145-165	9	212-0145-0000	-
160	155-175	9	212-0155-0000	-
170-175	165-185	9	212-0165-0000	-
180	175-195	9	212-0175-0000	-
190	185-205	9	212-0185-0000	-
200	195-215	9	212-0195-0000	-
215	205-225	12	212-0205-0000	-
225	215-235	12	212-0215-0000	-
250	245-265	12	212-0245-0000	-
275	265-285	12	212-0265-0000	-
280	275-295	12	212-0275-0000	-
300	295-315	12	212-0295-0000	-
315-325	315-325	12	212-0315-0000	-
350	345-385	12	212-0345-0000	-
380	375-415	12	212-0375-0000	-
400	395-435	12	212-0395-0000	-

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	AIRDUC®, PROTAPE®, CP ≥ 70 mm Order No.	CP Order No.
450	445-485	12	212-0445-0000	-
500	495-535	12	212-0495-0000	-

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on [www.norres.com](http://www.norres.com).

## Accessories

13.18.0



NORCONNECT 270-271